

# VITALIFT®

## LIFTING POINTS

Thiele lifting points serve to create a secure lifting or lashing point to enable safe handling and lashing activities.



### The TITAN Screw Type Lifting point XL TWN 1120 (EBLR)

has a freely movable coupling link and is capable of lifting its full working load limit in all directions. It rotates easily due to the special bush and guide plate.

- Grade 100 with 4:1 Safety factor
- 100% Magnetic crack tested
- BG approved

**WARNING: DOES NOT SWIVEL UNDER LOAD!**

### The X-TREME Screw Type Lifting Point XL TWN 1830 (EBLRTB)

is equipped with a ball bearing system. It is well suited for loads that have to be turned or flipped. It has a special wide coupling link which enables easy slinging of bigger hooks. The X-TREME Lifting point is not suitable for permanent rotations under load.

- Grade 100 with 4:1 Safety factor
- 100% Magnetic crack tested
- BG approved

**SWIVELS UNDER LOAD**



	Working Load Limits in (t)																			
	Marking	0.3	0.45	0.6	1.4	2.5	3.5	6.7	8	0.45	0.6	1.4	2.5	3.5	5.3	8	10	12.5	15	
	Screw Size	M8	M10	M12	M16	M20	M24	M30	M36	M10	M12	M16	M20	M24	M30	M36	M42	M48	M56	
	Thread Length	19mm	19mm	24mm	29mm	33mm	40mm	52mm	66mm	15mm	18mm	20mm	25mm	30mm	40mm	50mm	60mm	68mm	78mm	
	0°	1	0.3	0.45	0.6	2.1	3	6	7.1	0.9	1.2	2.8	5.3	7	10	15	18	20	25	
	90°	1	0.3	0.45	0.6	1.4	2.5	3.5	6.7	0.45	0.6	1.4	2.5	3.5	5.3	8	10	12.5	15	
	0-45°	2	0.42	0.63	0.85	2	3.55	5	9	0.63	0.85	2	3.55	5	7.5	11.2	14	17.5	21.2	
	45-60°	2	0.3	0.45	0.6	1.4	2.5	3.55	6.7	0.45	0.6	1.4	2.5	3.55	5.3	8	10	12.5	15	
	0-45°	3+4	0.63	0.95	1.25	3	5.3	7.1	14	0.95	1.25	3	5.3	7.1	11.2	17	21.2	26.5	31.5	
	45-60°	3+4	0.45	0.67	0.9	2.1	3.8	5.3	10	0.67	0.9	2.1	3.8	5.3	8	11.8	15	18.8	22.4	



# THIELE®



Made in Germany